



# Einhell

## EXPERT PLUS



Cordless Rotary Hammer

**HEROCCO**

Item No.: 4513900

Ident No.: 11017

Bar Code: 4006825630343

The Einhell cordless rotary hammer Herocco delivers more power and provides longer operation thanks to the brushless motor. Drilling, hammer drilling or chiseling with or without lock make it a valued allrounder. It is a member of the Power X-Change family. The pneumatic impact mechanism makes effortless progress through concrete. Tools can be changed quickly thanks to the universal SDS-plus tool chuck with auto-slip-in function. The ergonomic grip area provides a firm soft grip hold. The LED light illuminates the work area. Supplied with a magnetic bit adapter for screwing in a transport and storage case E-Box. The batteries and charger are available separately. For optimum operation it is recommended to use a 3.0 Ah battery or higher.

## Features & Benefits

- A member of the Power X-Change family
- Brushless motor - more power and prolonged operation
- 4 functions: Drilling/impact drilling/chiseling with and w/o lock
- Pneumatic impact mechanism for effortless drilling in concrete
- Universal SDS-plus chuck with semi-automatic function
- Speed electronics for fine adjustment on delicate jobs
- Low-vibration operations by vibration-cushioned main handle
- Ergonomic handle and additional handle with soft grip
- Infinitely adjustable drilling depth stop made of solid metal
- Incl. LED lamp to illuminate the work area
- Incl. magnetic bit adapter for screwing
- Recommendation for optimum results: 3.0 Ah battery & higher
- Supplied without battery and charger (available separately)
- Supplied in transport and storage case E-Box





## Technical Data

- Idle speed (gear 1)	0-1200 min <sup>-1</sup>
- Impact rate (gear 1)	0-5500 min <sup>-1</sup>
- Impact power	2.2 J
- Max. torque hard	18 Nm
- Drilling capacity in concrete	20 mm

## Logistic Data

- Pieces per export carton	4 Pieces
- Gross weight export carton	18.5 kg
- Tool weight	2.12 kg
- Gross Weight	4.38 kg
- Dimensions single packaging	400 x 360 x 120 mm
- Dimensions export carton	505 x 415 x 370 mm
- Container quantity (20"/40"/40"HC)	1248   2592   3024



## Available as special accessories



18V 30min Power X-Change  
Charger  
Item No.: 4512011  
Bar Code: 4006825587029  
Einhell Accessory



18V 5,2 Ah P-X-C Plus  
Battery  
Item No.: 4511437  
Bar Code: 4006825616606  
Einhell Accessory



Power-X-Boostcharger 6 A  
Charger  
Item No.: 4512064  
Bar Code: 4006825629019  
Einhell Accessory



Power-X-Twincharger 3 A  
Charger  
Item No.: 4512069  
Bar Code: 4006825629729  
Einhell Accessory



18V 2,0 Ah Power-X-Change  
Battery  
Item No.: 4511395  
Bar Code: 4006825610369  
Einhell Accessory



18V 4,0 Ah Power-X-Change  
Battery  
Item No.: 4511396  
Bar Code: 4006825610376  
Einhell Accessory



18V 3,0Ah PXC Starter Kit  
PXC-Starter-Kit  
Item No.: 4512041  
Bar Code: 4006825613698  
Einhell Accessory












18V 4,0Ah PXC Starter Kit  
PXC-Starter-Kit  
Item No.: 4512042  
Bar Code: 4006825613704  
Einhell Accessory

## Battery-Running-Times

screws (screw in 6x60 mm)

Usage	screwing	
Unit of measure	pieces	
with 1.5 Ah PXC	250	<div style="width: 25%; background-color: red;"></div>
with 2 Ah PXC	335	<div style="width: 33.5%; background-color: red;"></div>
with 2.5 Ah PXC	417	<div style="width: 41.7%; background-color: red;"></div>
with 2.6 Ah PXC+	430	<div style="width: 43%; background-color: red;"></div>
with 3 Ah PXC	500	<div style="width: 50%; background-color: red;"></div>
with 3.0 Ah PXC+	500	<div style="width: 50%; background-color: red;"></div>
with 4 Ah PXC	670	<div style="width: 67%; background-color: red;"></div>
with 5.2 Ah PXC+	870	<div style="width: 87%; background-color: red;"></div>
with 4-6 Ah PXC+ (4 Ah mode)	670	<div style="width: 67%; background-color: red;"></div>
with 4-6 Ah PXC+ (6 Ah mode)	100	<div style="width: 10%; background-color: red;"></div>
best performance with min.	3.0 Ah	
reason for best performance recommendation	current	

### holes (6x50 mm in concrete)

Usage	drilling	
Unit of measure	pieces	
with 1.5 Ah PXC	65	
with 2 Ah PXC	87	
with 2.5 Ah PXC	108	
with 2.6 Ah PXC+	113	
with 3 Ah PXC	130	
with 3.0 Ah PXC+	130	
with 4 Ah PXC	174	
with 5.2 Ah PXC+	225	
with 4-6 Ah PXC+ (4 Ah mode)	174	
with 4-6 Ah PXC+ (6 Ah mode)	260	